


perfectly balanced

Perfectly balanced components. Perfect spectral balance.

A perfect balance of power and detail. The Aragon Soundstage digital surround preamp and 8008X5 multi-channel power amp reproduce both music and movies with outstanding dynamics, depth and clarity.

Completely intuitive, the Aragon components are simple to set up and operate. And, the fully upgradeable architecture ensures that you always have the most advanced technology.

Aragon — a perfect balance of design and performance.



"Together this team offers an impressive package that is unstoppable in performance, fit and function. I put my name on the fact that you cannot better the overall performance of the Aragon combo..."

Gene DellaSala (GDS)
audioholics.com

MONDIAL



Mondial Designs
A Division of Klipsch Audio Technologies
914.693.8008
www.mondialdesigns.com

AMPLIFIERS

Palladium II

One-channel mono amplifier rated at 125W x 1 (Class A rating) / 400W x 1 (Class A/B rating) into 8 ohms with 0.02% THD or 600W x 1 into 4 ohms both from 5Hz-20kHz. Class A operation with Class A/B mode into 2 or 4 ohms. Balanced dual-differential design with 2 discrete amps in single chassis. Separate amplification of positive and negative balanced-input signals. 2,000-VA transformer. S/N 112dBA. 19" W x 6.5" H x 14.5" D, 75 lbs. \$5,500/pair U.S. MSRP

8008 x 5

Five-channel amplifier rated at 200W x 5 into 8 ohms or 400W x 5 into 4 ohms, both from 5Hz-20kHz with 0.05% THD. Solid-state. Bipolar design. DC-coupled output stage. Balanced or single-ended operation. S/N 110dBA. 19" W x 7.5" H x 23.625" D, 107 lbs. \$4,000 U.S. MSRP

8008 x 3 B

Three-channel amplifier rated at 200W x 3 into 8 ohms or 400W x 3 into 4 ohms, both from 5Hz-20kHz with 0.03% THD. DC Servo control. Balanced XLR and RCA single-ended inputs. S/N 110dBA. 19" W x 8" H x 16.5" D, 65 lbs. \$2,749 U.S. MSRP

8008 B B

Two-channel amplifier rated at 200W x 2 into 8 ohms or 400W x 2 into 4 ohms, both from 5Hz-20kHz with 0.03% THD. Dual-mono design. DC servo control. Balanced XLR and RCA single-ended inputs. S/N 110dBA. 19" W x 6.5" H x 14.5" D, 75 lbs. \$2,749 U.S. MSRP

8008 S T

Two-channel amplifier rated at 200W x 2 into 8 ohms or 400W x 2 into 4 ohms, both from 5Hz-20kHz with 0.03% THD. Dual-mono design. DC servo control. S/N 110dBA. 19" W x 6.5" H x 14.5" D, 70 lbs. \$2,249 U.S. MSRP

8002

Two-channel amplifier rated at 125W x 2 into 8 ohms or 250W x 2 into 4 ohms, both from 5Hz-20kHz with 0.03% THD. Dual-mono design. S/N 110dBA. 19" W x 6.5" H x 14.5" D, 22 lbs. \$1,599 U.S. MSRP

PREAMPLIFIERS

Soundstage

Digital surround preamp with Dolby Digital[®], DTS[®], Dolby ProLogic[®] and stereo modes. Eleven digital audio inputs, 8 stereo analog inputs, 6-channel external analog audio input, DVD audio input expansion slot, 8 composite and 8 S-video inputs, 6-channel XLR balanced and 6-channel RCA outputs, 2 composite and 2 S-video outputs, 1 Toslink digital output, 2 tape record outputs, 2-channel audio pass-thru, 6-channel DVD audio pass-thru, RS-232 port, I/R remote input, 5V trigger output and video expansion slot. Auto detection for all modes. Backlit learning remote control. 19" W x 6.75" H x 14" D, 38 lbs. \$4,000 U.S. MSRP

28K

Two-channel stereo preamplifier with 6 inputs, 2 line-level outputs and 2 tape outputs. Handcrafted fully discrete Class A design. Torodial power supply. Dual-mono DC supply rails. Direct-coupled output. Single switch contact in signal path. Gain stage with no output capacitors. Discrete transistor regulation for each channel. OFC for signal path and ground plane. Teflon[®]-dielectric wire between connectors and circuit board. Matched signal-path transistors. Silver switch contacts. Remote volume, mute, balance and power controls. Separate listen and record switches. FR 20Hz-20kHz \pm 0.1dB at 0.04% THD; S/N 100dBA; 8V max output. 19" W x 3.5" H x 11" D, 20 lbs. \$1,199 U.S. MSRP

47K

Phono preamplifier with external dual-mono DC power supply. Fully discrete Class A design. Matched transistors. No front-panel switches or gain controls. No power switch. Internal gain and load impedance adjustments via gold-to-gold shunting bars. FR 20Hz-20kHz \pm 0.3dB; S/N 86dBA MM; 10V max output. 19" W x 2.5" H x 10.5" D, 18 lbs. \$999 U.S. MSRP

DIGITAL TO ANALOG CONVERTERS

D2A2

D/A converter with dual Burr-Brown 20-bit D/A converters, Ultra Analog AES 21 receiver and HDCD decoding. One AES/EBU, one optical and two coaxial digital inputs. 0.005% THD; S/N 110dBA. 19" W x 3.5" H x 11" D, 20 lbs. \$999 U.S. MSRP